



SCHNELLARBEITSSTAHL



EN ISO 4957 / DIN 17350, gewalzt bzw. geschmiedet,
entkohlungsfrei geschliffen, poliert, Toleranzen nach hg.

Durchmesser: bis 5,00 mm = 2000 mm Länge (+/- 50 mm)
ab 5,00 mm = 3200 mm Länge (+/- 50 mm)

mm	kg/m	HS6-5-2-5 1.3243 geglüht	HS2-9-1-8 1.3247 geglüht	HS6-5-2 1.3343 geglüht	S1-5-2 1.3392 geglüht			
1	0,0			♦				
1,2	0,0			♦				
1,4	0,0			♦				
1,5	0,0			♦				
1,6	0,0			♦				
1,7	0,0			♦				
1,8	0,0			♦				
2	0,0			♦				
2,2	0,0	♦		♦				
2,3	0,0	♦		♦				
2,7	0,1	♦		♦				
2,8	0,1	♦		♦				
3,2	0,1	♦		♦	♦			
3,3	0,1	♦		♦	♦			
3,4	0,1			♦	♦			
3,5	0,1			♦	♦			
3,7	0,1	♦		♦	♦			
4,2	0,1	♦		♦	♦			
4,3	0,1	♦	♦	♦	♦			
4,4	0,1			♦				
4,5	0,1			♦				
4,7	0,1	♦		♦	♦			
5	0,2	♦		♦				
5,2	0,2	♦		♦	♦			
5,3	0,2	♦	♦	♦	♦			
5,4	0,2			♦				
5,5	0,2			♦				
5,7	0,2	♦		♦	♦			
5,8	0,2	♦		♦	♦			
6,2	0,2	♦		♦	♦			
6,3	0,3	♦	♦	♦	♦			
6,5	0,3			♦				
6,6	0,3			♦				
6,7	0,3	♦		♦	♦			
6,8	0,3	♦		♦	♦			



SCHNELLARBEITSSTAHL



EN ISO 4957 / DIN 17350, gewalzt bzw. geschmiedet,
entkohlungsfrei geschliffen, poliert, Toleranzen nach hg.

Durchmesser: bis 5,00 mm = 2000 mm Länge (+/- 50 mm)
ab 5,00 mm = 3200 mm Länge (+/- 50 mm)

mm	kg/m	HS6-5-2-5 1.3243 geglüht	HS2-9-1-8 1.3247 geglüht	HS6-5-2 1.3343 geglüht	S1-5-2 1.3392 geglüht			
8,7	0,47	♦		♦	♦			
9,2	0,52	♦	♦	♦	♦			
9,7	0,58	♦	♦	♦	♦			
10,2	0,7	♦		♦				
10,3	0,7	♦	♦	♦	♦			
10,7	0,7	♦		♦	♦			
10,8	0,7	♦		♦	♦			
11,2	0,8	♦		♦				
11,3	0,8	♦	♦	♦	♦			
11,8	0,9	♦		♦	♦			
12,2	0,9	♦		♦				
12,3	0,9	♦	♦	♦	♦			
12,7	1,0	♦		♦	♦			
12,8	1,0	♦		♦				
13	1,1	♦		♦				
13,2	1,1	♦		♦				
13,3	1,1	♦	♦	♦				