



SCHNELLARBEITSSTAHL



EN ISO 4957, gewalzt bzw. geschmiedet, geblüht, gerichtet,
geschält/poliert bzw. überdreht/geschält.

Toleranzen: bis 50,00 mm rund = k11

ab 50,00 mm rund = -0/+1 mm

Durchmesser: bis 45,00 mm = 2900 - 3200 mm Länge

ab 45,00 mm = 3000 - 4000 mm Länge

mm	kg/m	HS6-5-2-5 1.3243 geblüht	HS2-9-1-8 1.3247 geblüht	HS6-5-2 1.3343 geblüht				
14,2	1,3			♦				
14,3	1,3	♦		♦				
14,7	1,3			♦				
15,2	1,4	♦		♦				
15,7	1,5			♦				
16,2	1,6	♦	♦	♦				
16,7	1,7			♦				
17,2	1,8			♦				
18,2	2,1	♦	♦	♦				
18,7	2,2			♦				
19,2	2,3	♦		♦				
20,2	2,5	♦	♦	♦				
20,5	2,6	♦		♦				
21,2	2,8	♦		♦				
22,2	3,1	♦		♦				
23,2	3,3	♦		♦				
24,2	3,6	♦		♦				
25,2	3,9	♦	♦	♦				
26,2	4,3	♦	♦	♦				
27,2	4,6			♦				
28,2	4,9	♦		♦				
29,2	5,3			♦				
30,2	5,7	♦		♦				
30,5	5,8	♦		♦				
31,2	6,0	♦	♦	♦				
32,2	6,4	♦		♦				
33,2	6,8	♦		♦				
34,2	7,3	♦		♦				
35,2	7,7	♦	♦	♦				
36,2	8,1	♦		♦				
38,2	9,0	♦		♦				
40,2	10,0	♦		♦				
40,5	10,2	♦	♦	♦				



SCHNELLARBEITSSTAHL



EN ISO 4957, gewalzt bzw. geschmiedet, geblüht, gerichtet,
geschält/poliert bzw. überdreht/geschält.

Toleranzen: bis 50,00 mm rund = k11

ab 50,00 mm rund = -0/+1 mm

Durchmesser: bis 45,00 mm = 2900 - 3200 mm Länge

ab 45,00 mm = 3000 - 4000 mm Länge

mm	kg/m	HS6-5-2-5	HS2-9-1-8	HS6-5-2				
		1.3243 geblüht	1.3247 geblüht	1.3343 geblüht				
41,2	10,5	♦	♦	♦				
42,2	11,0			♦				
43,2	11,6	♦		♦				
45,2	12,7	♦		♦				
46,2	13,2			♦				
48,2	14,4			♦				
50,2	15,6			♦				
51,2	16,3	♦	♦	♦				
55,8	19,3	♦	♦	♦				
61,2	23,2	♦	♦	♦				
65,8	26,8	♦	♦	♦				
68,2	28,8			♦				
70,2	30,6	♦	♦	♦				
75	34,9	♦	♦	♦				
81	40,7	♦	♦	♦				
85	44,8			♦				
91	51,3	♦	♦	♦				
95	56,0			♦				
102	64,5	♦	♦	♦				
105	68,4			♦				
111	76,4	♦	♦	♦				
121	90,8	♦	♦	♦				
128	101,6			♦				
132	108,0	♦	♦	♦				
142	125,0	♦	♦	♦				
152	143,2	♦	♦	♦				
162	162,7			♦				
182	205,4			♦				
192	228,6			♦				
202	253,0			♦				
252	393,7			♦				
303	569,2			♦				