



GESENKSTAHL



EN ISO 4957 / DIN 17350, GEWALZT BZW. GESCHMIEDET
GEGLÜHT, GESCHÄLT BZW. ÜBERDREHT, TOLERANZEN NACH EN 10060,
STABLÄNGEN VON 3 - 5 M

| MM | KG/M | 55NiCrMoV7 1.2714 GEGLÜHT | 55NiCrMoV7 1.2714 VERGÜTET |
|-----|-------|---------------------------------|----------------------------------|
| 20 | 2,5 | ♦ | ♦ |
| 25 | 3,9 | ♦ | ♦ |
| 30 | 5,6 | ♦ | ♦ |
| 35 | 7,6 | ♦ | ♦ |
| 40 | 9,9 | ♦ | ♦ |
| 46 | 13,1 | ♦ | ♦ |
| 48 | 14,3 | | |
| 50 | 15,5 | | |
| 51 | 16,1 | ♦ | ♦ |
| 56 | 19,4 | ♦ | ♦ |
| 61 | 23,1 | ♦ | ♦ |
| 66 | 27,0 | ♦ | ♦ |
| 71 | 31,3 | ♦ | ♦ |
| 76 | 35,8 | ♦ | ♦ |
| 81 | 40,7 | ♦ | ♦ |
| 86 | 45,9 | ♦ | ♦ |
| 91 | 51,3 | ♦ | ♦ |
| 96 | 57,1 | ♦ | ♦ |
| 101 | 63,2 | ♦ | ♦ |
| 106 | 69,7 | ♦ | ♦ |
| 111 | 76,4 | ♦ | ♦ |
| 116 | 83,4 | ♦ | ♦ |
| 121 | 90,8 | ♦ | ♦ |
| 126 | 98,4 | ♦ | ♦ |
| 131 | 106,4 | ♦ | ♦ |
| 136 | 114,7 | ♦ | ♦ |
| 141 | 123,3 | ♦ | ♦ |
| 146 | 132,2 | ♦ | ♦ |
| 152 | 143,2 | ♦ | ♦ |
| 157 | 152,8 | ♦ | ♦ |
| 162 | 162,7 | ♦ | ♦ |
| 167 | 172,9 | ♦ | ♦ |
| 172 | 183,4 | ♦ | ♦ |

♦ = STANDARD ABMESSUNGEN



GESENKSTAHL



EN ISO 4957 / DIN 17350, GEWALZT BZW. GESCHMIEDET
GEGLÜHT, GESCHÄLT BZW. ÜBERDREHT, TOLERANZEN NACH EN 10060,
STABLÄNGEN VON 3 - 5 M

| MM | KG/M | 55NiCrMoV7 1.2714 GEGLÜHT | 55NiCrMoV7 1.2714 VERGÜTET |
|-----|-------|---------------------------------|----------------------------------|
| 177 | 194,2 | ♦ | ♦ |
| 182 | 205,4 | ♦ | ♦ |
| 187 | 216,8 | ♦ | ♦ |
| 192 | 228,6 | ♦ | ♦ |
| 197 | 240,6 | ♦ | ♦ |
| 202 | 253,0 | ♦ | ♦ |
| 207 | 265,7 | ♦ | ♦ |
| 212 | 278,7 | ♦ | ♦ |
| 217 | 292,0 | ♦ | ♦ |
| 222 | 305,6 | ♦ | ♦ |
| 227 | 319,5 | ♦ | ♦ |
| 232 | 333,7 | ♦ | ♦ |
| 237 | 348,2 | ♦ | ♦ |
| 242 | 363,1 | ♦ | ♦ |
| 247 | 378,3 | ♦ | ♦ |
| 252 | 393,7 | ♦ | ♦ |
| 257 | 409,5 | ♦ | ♦ |
| 262 | 425,6 | ♦ | ♦ |
| 267 | 442,0 | ♦ | ♦ |
| 272 | 458,7 | ♦ | ♦ |
| 277 | 475,7 | ♦ | ♦ |
| 282 | 493,0 | ♦ | ♦ |
| 287 | 510,7 | ♦ | ♦ |
| 292 | 528,6 | ♦ | ♦ |
| 297 | 546,9 | ♦ | ♦ |
| 303 | 569,2 | | ♦ |
| 308 | 588,2 | | ♦ |
| 313 | 607,4 | | ♦ |
| 323 | 646,8 | | ♦ |
| 333 | 687,5 | ♦ | ♦ |
| 343 | 729,4 | ♦ | ♦ |
| 353 | 772,6 | ♦ | ♦ |
| 363 | 817,0 | ♦ | ♦ |



GESENKSTAHL



EN ISO 4957 / DIN 17350, GEWALZT BZW. GESCHMIEDET
GEGLÜHT, GESCHÄLT BZW. ÜBERDREHT, TOLERANZEN NACH EN 10060,
STABLÄNGEN VON 3 - 5 M

| MM | KG/M | 55NiCrMoV7 | 55NiCrMoV7 | |
|------|--------|-------------------|--------------------|--|
| | | 1.2714 GEGLÜHT | 1.2714 VERGÜTET | |
| 373 | 862,6 | ♦ | ♦ | |
| 383 | 909,5 | ♦ | ♦ | |
| 393 | 957,6 | ♦ | ♦ | |
| 403 | 1006,9 | ♦ | ♦ | |
| 413 | 1057,5 | ♦ | ♦ | |
| 423 | 1109,4 | ♦ | ♦ | |
| 433 | 1162,4 | ♦ | ♦ | |
| 443 | 1216,7 | ♦ | ♦ | |
| 453 | 1272,3 | ♦ | ♦ | |
| 463 | 1329,1 | ♦ | ♦ | |
| 473 | 1387,1 | ♦ | ♦ | |
| 483 | 1446,4 | ♦ | ♦ | |
| 493 | 1506,9 | ♦ | ♦ | |
| 503 | 1568,7 | ♦ | ♦ | |
| 513 | 1631,6 | ♦ | ♦ | |
| 523 | 1695,9 | ♦ | ♦ | |
| 533 | 1761,4 | ♦ | ♦ | |
| 543 | 1828,1 | ♦ | ♦ | |
| 553 | 1896,0 | ♦ | ♦ | |
| 563 | 1965,2 | ♦ | ♦ | |
| 573 | 2035,6 | ♦ | ♦ | |
| 583 | 2107,3 | ♦ | ♦ | |
| 593 | 2180,2 | ♦ | ♦ | |
| 635 | 2500,0 | ♦ | | |
| 685 | 2909,2 | ♦ | | |
| 705 | 3081,6 | ♦ | | |
| 725 | 3258,9 | ♦ | | |
| 755 | 3534,2 | ♦ | | |
| 805 | 4017,8 | ♦ | | |
| 855 | 4532,4 | ♦ | | |
| 905 | 5022,0 | ♦ | | |
| 925 | 5304,9 | ♦ | | |
| 1000 | 6200,0 | ♦ | | |

♦ = STANDARD ABMESSUNGEN