



Stock Program PM-Steel



Grade			OB-PM-K49	OB-PM-S79	OB-PM-S59	OB-PM-S39	OB-PM-M39
Dimensions in mm	Profile	Tolerance	Stock standard				
<b>Round bars</b>							
Ø 3,70	●	h9			•		
Ø 3,90	●	h9			•		
Ø 5,30	●	h9			•		
Ø 6,30	●	h9			•		
Ø 6,40	●	h9			•		
Ø 7,30	●	h9			•		
Ø 8,30	●	h9			•		
Ø 10,30	●	h9			•		
Ø 12,30	●	h9			•		
Ø 14,50	●	k11			•		
Ø 16,50	●	k11	•	•	•		•
Ø 18,50	●	k11		•			•
Ø 20,50	●	k11		•	•	•	•
Ø 22,50	●	k11		•	•	•	
Ø 24,50	●	k11			•	•	
Ø 25,50	●	k11	•		•	•	•
Ø 26,50	●	k11		•	•		
Ø 28,50	●	k11		•	•		
Ø 30,80	●	k11		•	•	•	
Ø 33,00	●	k11		•	•		
Ø 35,80	●	k11	•	•	•		•
Ø 38,80	●	k11		•	•		
Ø 39,80	●	k11			•	•	
Ø 40,80	●	k11	•				•
Ø 42,80	●	k11			•	•	
Ø 43,80	●	k11		•	•	•	
Ø 45,80	●	k11					•
Ø 46,80	●	k11		•	•		•
Ø 48,80	●	k11		•	•		
Ø 50,80	●	k14	•				



Stock Program PM-Steel



Grade			OB-PM-K49	OB-PM-S79	OB-PM-S59	OB-PM-S39	OB-PM-M39
Dimensions in mm	Profile	Tolerance	Stock standard				
Ø 55,80	●	k14					•
Ø 60,80	●	k14	•				•
Ø 65,80	●	k14					•
Ø 67,00	●	k14			•		
Ø 71,00	●	k14	•		•	•	•
Ø 76,00	●	k14		•			•
Ø 81,00	●	k14	•	•		•	•
Ø 86,00	●	k14		•	•		•
Ø 91,00	●	k14	•				•
Ø 96,00	●	k14					•
Ø 101,80	●	k14	•		•	•	•
Ø 111,80	●	k15	•	•	•	•	•
Ø 121,80	●	k14	•	•	•	•	•
Ø 128,00	●	k14					
Ø 202,00	●	k14	•				
<b>Square bars</b>							
150,00 x 150,00	■	-0/+2 mm		•			
200,00 x 200,00	■	-0/+2 mm		•			
250,00 x 250,00	■	-0/+2 mm		•			
<b>Flat bars</b>							
208,00 x 122,00	▬	-0/+2 mm		•			
250,00 x 60,00	▬	-0/+2 mm	•				
250,00 x 80,00	▬	-0/+2 mm	•				
250,00 x 100,00	▬	-0/+2 mm	•				
250,00 x 120,00	▬	-0/+2 mm	•				
250,00 x 150,00	▬	-0/+2 mm	•				
300,00 x 200,00	▬	-0/+2 mm	•	•	•	•	
400,00 x 200,00	▬	-0/+2 mm		•		•	
500,00 x 200,00	▬	-0/+2 mm		•		•	